JAMO STUDIO SERIES • S 628



Specifications

System Type
Tweeter (mm/in)
Midrange (mm/in)
Woofer (mm/in)
Frequency Response (Hz +/- 3 dB)
Power Handling (Watts Long/Short Term)

Sensitivity (dB, 2.8V/1m)

Impedance (Ohm)

Product Dimensions (mm/in, HxWxD)

Weight (Kg/lb)

Finishes

S 628

3 Way Bass Reflex

25 / 1

Three: 127 / 5

254 / 10

37-20,000

150 / 240

90

6

1134 x 190 x 380 /

44.6 x 7.5 x 15.0

25.5 / 56.2

Black Ash, White Ash,

Dark Apple

Design

The Jamo S 628 is the flagship speaker of the Studio 600 Series. It's crystal clear, room–filling sound comes from its 3-way design highlighting three midrange drivers and a side-mounted 10-inch woofer. S 628 "mirror image" pairs give you both a slimmer design and placement flexibility for the best possible acoustic interaction with your listening room. The S 628 is available in White Ash, Dark Apple and Black Ash finishes with soft-feel black baffles for a premium, contemporary appearance. Equipped for optional biwiring/bi-amplification and includes optional speaker spikes.

Technology

- 1-inch (25 cm) soft dome tweeter/three 5-inch (127 cm) aluminized midrange drivers/10-inch (254 cm) side-firing woofer.
- Bass-reflex design with dual flared, rear-firing ports: Increases speaker efficiency and bass output.
- Waveguide: Provides more uniform dispersion from 2-10 kHz. Dynamics and clarity are enhanced while distortion is significantly reduced.
- Aluminum centre-plug: Eliminates cone breakup for faster "attack" and increased vocal clarity. Additional voice-coil cooling reduces power compression.
- Aluminized midrange drivers: Increases cone rigidity and vocal clarity.
- Side-firing woofer: Provides a slim, cohesive cabinet design and bass optimization for varying room acoustics.
- Dual, 5-way binding posts: Allows bi-wiring/bi-amplification with multiple connection options with wire up to 12 gauge (AWG).

